

Dehumidifier

HEPA Air Scrubber



HP125

Water Removal Capacity

150 Pints/day
(18.75 gallons)
(90°F, 90%RH)

Construction/Abatement/Water Damage HEPA 3-Stage High Volume 0.3 microns

Removal of airborne hazardous materials

- Crystalline Silica • Lead • Mold Spores
- Pollen • Bacteria • Airborne Particles

“Don't just dry it, purify it!”

Adapter Kit **HPA125** attaches to the Dehumidifier allowing the 15' Ducting Hose **HP815** to fit, connecting to the HEPA Air Scrubber. This system effectively removes moisture, toxins and contaminants for a clean environment.

- The perfect machine for water damage restoration, and air drying applications.
- Maximizes water extraction.
- Compact design for easy storage.
 - Durable construction withstands rough handling.
 - Semi-pneumatic wheels for easy transport and maneuvering on job sites.
- When used with the 3-Stage HEPA Air Purifier, removes toxins, debris, contaminants and moisture from the air, resulting in cleaner and drier air that is healthier to breathe and much more comfortable to work in.

DEHUMIDIFIER SPECS

WATER REMOVAL CAPACITY	76 Pints/Day at AHAM (80°F, 60% RH) 150 Pints/Day (90°F, 90% RH)
TYPE	Standard Refrigerant (R410A)
VOLTS/HERTZ	115V / 60Hz
POWER	7.3 Amps
OPERATING RANGE	33° - 100°F (1° - 38°C)
UNIT / BOX WEIGHT	81 lbs. / 90 lbs.
UNIT / BOX DIMENSIONS (LxWxH)	20"x19"x32" / 22"x21"x24"
POWER CORD LENGTH	25 ft.
FILTER	High Airflow Filter (HAF)
SAFETY CERTIFICATION	ETL/CETL Certified



AIR IN

HP3400A

Adapter Kit **HPA125**
DUCTING HOSE **HP815**
15' Length x 8" I.D. Diameter

HEPA 3 STAGE AIR SCRUBBER



- HEPA Filter Change Light
- Durable & Rugged ABS Housing Construction Design
- Latch
- Larger & Wider Air Outlet
- Variable Speed Control Switch
- Auxiliary Outlets (GFCI) with Circuit Breaker
- Wrap Around Cord Design
- Removable Foam Cap
- Stackable (5 units High)

VOLTS/CYCLE	115V/60Hz	HOUSING	Injection Mold ABS Plastic Housing Materials
MOTOR	1/2 HP	DUCT SIZES (AIR OUTLET DIMENSIONS)	5" X 10.8"
AMP	2.8 Amps (On Highest Speed)	GFCI DAISY CHAIN	Yes - Plug 4 units together
RATED AIRFLOW	700 CFM	FILTER SYSTEM	3-STAGE
SPEEDS	Variable Speed Control	1ST STAGE FILTER	HP816 - 16" x 16" Washable Nylon Mesh Filter
RPM (LOW-HIGH)	850-2900 RPM	2ND STAGE FILTER	HP16 - 16" x 16" Pleated Media Filter
UNIT WEIGHT	27.6 lbs.	3RD STAGE FILTER	HP50 - 16" x 16" x 2" Thick HEPA Filter
UNIT DIMENSIONS (LxWxH)	19.6" x 12.3" x 21.6"	FILTER CHANGE LIGHT	Indicates when primary HEPA filter needs to be changed
BOX WEIGHT	33.6 lbs.	STACKABLE	Yes - Up to 5 units high
BOX DIMENSIONS (LxWxH)	21.3" x 14" x 23"	SAFETY CERTIFICATIONS	ETL/CETL (Equivalent to UL/CUL, CSA & NOM)

CONFINED SPACE VENTILATOR FAN



- VARIABLE SPEED CONTROL
- 2500 CFM**
- HP12V**

- Offers complete control of air velocity and volume with a variable speed control switch.
- 12" diameter flex hose ducts air up to 125 ft.
- Can be used without hoses for high volume air circulation in gyms, hallways and other large areas.
- Low amp, powerful sealed motor efficiently delivers dry air to complete any drying process.

SPECIFICATIONS

VOLTS/CYCLE	115V/60Hz
MOTOR	1/2 HP SEALED MOTOR
MAXIMUM RATED AIRFLOW	2,500 CFM
POWER	4.5A (HIGHEST SPEED)
SPEED	VARIABLE SPEED CONTROL
RPM (LOW-HIGH)	1200 / 3200 RPM
UNIT / BOX WEIGHT	23.1 LBS. / 26 LBS.
UNIT / BOX DIMENSIONS (L x W x H)	15"x13.6"x18" 15.7"x14.2"x19.1"
CORD LENGTH / GAUGE	20 FT. / 18AWG
AIR OUTLET DIAMETER	12 INCHES
HOUSING MATERIAL	ABS PLASTIC HOUSING (INJECTION MOLD)
SAFETY CERTIFICATIONS	ETL/CETL CERTIFIED



**12" Ø x 25' LONG DUCT HOSE
HP25**